

Upgrading from the glossary package to the glossaries package

Nicola L.C. Talbot

2017-06-11

Abstract

The purpose of this document is to provide advice if you want to convert a L^AT_EX document from using the obsolete glossary package to the replacement glossaries package.

Contents

1 Why the Need for a New Package?	2
2 Package Options	3
3 Defining new glossary types	4
4 \make<<i>glossary name</i>>	5
5 Storing glossary information	5
6 Adding an entry to the glossary	6
6.1 \useglosentry	6
6.2 \useGlosentry	6
6.3 \gls	7
6.4 \glossary	7
7 Acronyms	8
7.1 \acrln and \acrsh	9
7.2 \ifacronymfirstuse	10
7.3 \resetacronym and \unsetacronym	10
8 Displaying the glossary	12
9 Processing Your Document	13

1 Why the Need for a New Package?

The glossary package started out as an example in a tutorial, but I decided that I may as well package it up and upload it to CTAN. Unfortunately it was fairly rigid and unable to adapt well to the wide variation in glossary styles. Users began making requests for enhancements, but with each enhancement the code became more complicated and bugs crept in. Each fix in one place seemed to cause another problem elsewhere. In the end, it was taking up too much of my time to maintain, so I decided to replace it with a much better designed package. With the new glossaries package:

- you can define irregular plurals;
- glossary terms can have an associated symbol in addition to the name and description;
- new glossary styles are much easier to design;
- you can add dictionaries to supply translations for the fixed names used in headings and by some of the glossary styles;
- you can choose¹ between using `makeindex` or `xindy` to sort the glossary. Using `xindy` means that:
 - there is much better support for terms containing accented or non-Latin characters;
 - there is support for non-standard location numbers;
- you don't need to remember to escape `makeindex`'s special characters as this is done internally;
- hierarchical entries and homographs are supported;²
- there is better support for cross-referencing glossary entries;
- acronyms are just another glossary term which helps to maintain consistency;
- different acronym styles are supported.

¹as from v1.17. Previous versions were designed to be used with `makeindex` only

²as from v1.17

2 Package Options

When converting a document that currently uses the obsolete glossary package to the replacement glossaries package, it should be fairly obvious that the first thing you need to do is replace `\usepackage{glossary}` with `\usepackage{glossaries}`, however some of the package options are different, so you may need to change those as well. Table 1 shows the mappings from the glossary to the glossaries package options.

Table 1: Mappings from glossary to glossaries package options

glossary option	glossaries option
<code>style=list</code>	<code>style=list</code>
<code>style=altlist</code>	<code>style=altlist</code>
<code>style=long,header=none,border=none,cols=2</code>	<code>style=long</code>
<code>style=long,header=plain,border=none,cols=2</code>	<code>style=longheader</code>
<code>style=long,header=none,border=plain,cols=2</code>	<code>style=longborder</code>
<code>style=long,header=plain,border=plain,cols=2</code>	<code>style=longheaderborder</code>
<code>style=long,header=none,border=none,cols=3</code>	<code>style=long3col</code>
<code>style=long,header=plain,border=none,cols=3</code>	<code>style=long3colheader</code>
<code>style=long,header=none,border=plain,cols=3</code>	<code>style=long3colborder</code>
<code>style=long,header=plain,border=plain,cols=3</code>	<code>style=long3colheaderborder</code>
<code>style=super,header=none,border=none,cols=2</code>	<code>style=super</code>
<code>style=super,header=plain,border=none,cols=2</code>	<code>style=superheader</code>
<code>style=super,header=none,border=plain,cols=2</code>	<code>style=superborder</code>
<code>style=super,header=plain,border=plain,cols=2</code>	<code>style=superheaderborder</code>
<code>style=super,header=none,border=none,cols=3</code>	<code>style=super3col</code>
<code>style=super,header=plain,border=none,cols=3</code>	<code>style=super3colheader</code>
<code>style=super,header=none,border=plain,cols=3</code>	<code>style=super3colborder</code>
<code>style=super,header=plain,border=plain,cols=3</code>	<code>style=super3colheaderborder</code>
<code>number=none</code>	<code>nonumberlist</code>
<code>number=<counter name></code>	<code>counter=<counter name></code>
<code>toc</code>	<code>toc</code>
<code>hypertoc</code>	<code>toc</code>
<code>hyper</code>	<i>no corresponding option</i>
<code>section=true</code>	<code>section</code>
<code>section=false</code>	<i>no corresponding option</i>
<code>acronym</code>	<code>acronym</code>
<code>global</code>	<i>no corresponding option</i>

3 Defining new glossary types

If you have created new glossary types, you will need to replace all instances of

```
\newglossarytype[⟨log-ext⟩]{⟨type⟩}{⟨out-ext⟩}{⟨in-ext⟩}[⟨old
style list⟩]

\newcommand{\⟨type⟩name}{⟨title⟩}
```

glossary

with

```
\newglossary[⟨log-ext⟩]{⟨type⟩}{⟨out-ext⟩}{⟨in-ext⟩}{⟨title⟩}
```

glossaries

in the preamble, and, if the new glossary requires a different style to the main (default) glossary, you will also need to put

```
\glossarystyle{⟨new style⟩}
```

glossaries

immediately before the glossary is displayed, or you can specify the style when you display the glossary using `\printglossary` (see below).

The `⟨old style list⟩` optional argument can be converted to `⟨new style⟩` using the same mapping given in Table 1.

For example, if your document contains the following:

```
\newglossarytype[nlg]{notation}{not}{ntn}[style=long,header]
\newcommand{\notationname}{Index of Notation}
```

You will need to replace the above two lines with:

```
\newglossary[nlg]{notation}{not}{ntn}{Index of Notation}
```

in the preamble and

```
\glossarystyle{longheader}
```

immediately prior to displaying this glossary. Alternatively, you can specify the style using the `style` key in the optional argument of `\printglossary`. For example:

```
\printglossary[type=notation,style=longheader]
```

Note that the glossary title is no longer specified using `\⟨glossary-type⟩name` (except for `\glossaryname` and `\acronymname`) but is instead specified in the `⟨title⟩` argument of `\newglossary`. The short title which is specified in the glossary package by the command `\short⟨glossary-name⟩name` is now specified using the `toctitle` key in the optional argument to `\printglossary`.

4 \make<glossary name>

All instances of `\make<glossary name>` (e.g. `\makeglossary` and `\makeacronym`) should be replaced by the single command `\makeglossaries`. For example, if your document contained the following:

```
\makeglossary  
\makeacronym
```

then you should replace both lines with the single line:

```
\makeglossaries
```

5 Storing glossary information

With the old glossary package you could optionally store glossary information for later use, or you could simply use `\glossary` whenever you wanted to add information to the glossary. With the new glossaries package, the latter option is no longer available.³ If you have stored all the glossary information using `\storeglosentry`, then you will need to convert these commands into the equivalent `\newglossaryentry`. If you have only used `\glossary`, then see Section 6.4.

Substitute all instances of

```
\storeglosentry{\label}{\gls-entry}
```

glossary

with

```
\newglossaryentry{\label}{\gls-entry}
```

glossaries

This should be fairly easy to do using the search and replace facility in your editor (but see notes below).

If you have used the optional argument of `\storeglosentry` (i.e. you have multiple glossaries) then you will need to substitute

```
\storeglosentry[\gls-type]{\label}{\gls-entry}
```

glossary

with

```
\newglossaryentry{\label}{\gls-entry}, type=\gls-type
```

glossaries

³mainly because having a key value list in `\glossary` caused problems, but it also helps consistency.

The glossary entry information `<gls-entry>` may also need changing. If `<gls-entry>` contains any of `makeindex`'s special characters (i.e. @ ! " or |) then they should no longer be escaped with " since the `glossaries` package deals with these characters internally. For example, if your document contains the following:

```
\storeglosentry{card}{name={$|\mathcal{S}|$},  
description={The cardinality of the set $\mathcal{S}$}}
```

then you will need to replace it with:

```
\newglossaryentry{card}{name={$|\mathcal{S}|$},  
description={The cardinality of the set $\mathcal{S}$}}
```

The `format` and `number` keys available in `\storeglosentry` are not available with `\newglossaryentry`.

6 Adding an entry to the glossary

The `glossary` package provided two basic means to add information to the glossary: firstly, the term was defined using `\storeglosentry` and the entries for that term were added using `\useglosentry`, `\useGlosentry` and `\gls`. Secondly, the term was added to the glossary using `\glossary`. This second approach is unavailable with the `glossaries` package.

6.1 \useglosentry

The `glossary` package allows you to add information to the glossary for a predefined term without producing any text in the document using

```
\useglosentry[<old options>]{<label>}
```

glossary

Any occurrences of this command will need to be replaced with

```
\glsadd[<new options>]{<label>}
```

glossaries

The `format` key in `<old options>` remains the same in `<new options>`. However the `number=<counter name>` key in `<old options>` should be replaced with `counter=<counter name>` in `<new options>`.

6.2 \useGlosentry

The `glossary` package allows you to add information to the glossary for a predefined term with the given text using

```
\useGlosentry[⟨old options⟩]{⟨label⟩}{⟨text⟩}
```

glossary

Any occurrences of this command will need to be replaced with

```
\glslink[⟨new options⟩]{⟨label⟩}{⟨text⟩}
```

glossaries

The mapping from ⟨old options⟩ to ⟨new options⟩ is the same as that given Section 6.1.

6.3 \gls

Both the glossary and the glossaries packages define the command \gls. In this case, the only thing you need to change is the number key in the optional argument to counter. Note that the new form of \gls also takes a final optional argument which can be used to insert text into the automatically generated text.

6.4 \glossary

When using the glossaries package, you should not use \glossary directly.⁴ If, with the old package, you have opted to explicitly use \glossary instead of storing the glossary information with \storeglosentry, then converting from glossary to glossaries will be more time-consuming, although in the end, I hope you will see the benefits.⁵ If you have used \glossary with the old glossary package, you will instead need to define the relevant glossary terms using \newglossaryentry and reference the terms using \glsadd, \glslink, \gls etc.

If you don't like the idea of continually scrolling back to the preamble to type all your \newglossaryentry commands, you may prefer to create a new file, in which to store all these commands, and then input that file in your document's preamble. Most text editors and front-ends allow you to have multiple files open, and you can tab back and forth between them.

⁴This is because \glossary requires the argument to be in a specific format and doesn't use the ⟨key⟩=⟨value⟩ format that the old glossary package used. The new package's internal commands set this format, as well as escaping any of makeindex's or xindy's special characters. What's more, the format has changed as from v1.17 to allow the new package to be used with either makeindex or xindy.

⁵From the user's point of view, using \glossary throughout the document is time consuming, and if you use it more than once for the same term, there's a chance extra spaces may creep in which will cause makeindex to treat the two entries as different terms, even though they look the same in the document.

7 Acronyms

In the glossary package, acronyms were treated differently to glossary entries. This resulted in inconsistencies and sprawling unmaintainable code. The new glossaries package treats acronyms in exactly the same way as normal glossary terms. In fact, in the glossaries package, the default definition of:

```
\newacronym[⟨options⟩]{⟨label⟩}{⟨abbrv⟩}{⟨long⟩}
```

glossaries

is a shortcut for:

```
\newglossaryentry{⟨label⟩}{type=\acronymtype,
name={⟨abbrv⟩},
description={⟨long⟩},
text={⟨abbrv⟩},
first={⟨long⟩ ⟨abbrv⟩},
plural={⟨abbrv⟩s},
firstplural={⟨long⟩s ⟨abbrv⟩s},
⟨options⟩}
```

glossaries

This is different to the glossary package which set the name key to *⟨long⟩* (*⟨abbrv⟩*) and allowed you to set a description using the *description* key. If you still want to do this, you can use the *description* package option, and use the *description* key in the optional argument of `\newacronym`.

For example, if your document originally had the following:

```
\newacronym{SVM}{Support Vector Machine}{description=Statistical
pattern recognition technique}
```

Then you would need to load the glossaries package using the *description* package option, for example:

```
\usepackage[description]{glossaries}
```

and change the acronym definition to:

```
\newacronym[description=Statistical pattern recognition
technique]{svm}{SVM}{Support Vector Machine}
```

You can then reference the acronym using any of the new referencing commands, such as `\gls` or `\glsadd`.

With the old glossary package, when you defined an acronym, it also defined a command `\acr-name` which could be used to display the acronym in the text. So the above

SVM example would create the command `\SVM` with the old package. In the new glossaries package, the acronyms are just another type of glossary entry, so they are displayed using `\gls{<label>}`. Therefore, in the above example, you will also need to replace all occurrences of `\SVM` with `\gls{svm}`.

If you have used `\useacronym` instead of `\<acr-name>`, then you will need to replace all occurrences of

```
\useacronym[<insert>]{<acr-name>}
```

glossary

with

```
\gls{<label>} [<insert>]
```

glossaries

Note that the starred versions of `\useacronym` and `\<acr-name>` (which make the first letter uppercase) should be replaced with `\Gls{<label>}`.

Alternatively (as from v1.18 of the glossaries package), you can use `\oldacronym` which uses the same syntax as the old glossary package's `\newacronym` and also defines `\<acr-name>`. For example, if your document originally had the following:

```
\newacronym{SVM}{Support Vector Machine}{description=Statistical  
pattern recognition technique}
```

glossary

then you can change this to:

```
\oldacronym{SVM}{Support Vector Machine}{description=Statistical  
pattern recognition technique}
```

glossaries

You can then continue to use `\SVM`. However, remember that L^AT_EX generally ignores spaces after command names that consist of alphabetical characters. You will therefore need to force a space after `\<acr-name>`, unless you also load the `xspace` package. (See Section 13 of the glossaries documentation for further details.) Note that `\oldacronym` uses its first argument to define the acronym's label (as used by commands like `\gls`), so in the above example, with the new glossaries package, `\SVM` becomes a shortcut for `\gls{SVM}` and `\SVM*` becomes a shortcut for `\Gls{SVM}`.

7.1 `\acrln` and `\acrsh`

In the glossary package, it is possible to produce the long and short forms of an acronym without adding an entry to the glossary using `\acrln` and `\acrsh`. With the glossaries package (provided you defined the acronym using `\newacronym` or `\oldacronym` and provided you haven't redefined `\newacronym`) you can replace

```
\acrsh{\acr-name}
```

glossary

with

```
\acrshort{\label}
```

glossaries

and you can replace

```
\acrln{\acr-name}
```

glossary

with

```
\acrlong{\label}
```

glossaries

The `glossaries` package also provides the related commands `\acrshortpl` (plural short form) and `\acrlongpl` (plural long form) as well as upper case variations. If you use the `glossaries` “shortcuts” package option, you can use `\acs` in place of `\acrshort` and `\acl` in place of `\acrlong`.

See Section 13 of the `glossaries` manual for further details of how to use these commands.

7.2 `\ifacronymfirstuse`

The `glossary` package command

```
\ifacronymfirstuse{\acr-name}{\text1}{\text2}
```

glossary

can be replaced by the `glossaries` command:

```
\ifglsused{\label}{\text2}{\text1}
```

glossaries

Note that `\ifglsused` evaluates the opposite condition to that of `\ifacronymfirstuse` which is why the last two arguments have been reversed.

7.3 `\resetacronym` and `\unsetacronym`

The `glossary` package allows you to reset and unset the acronym flag which is used to determine whether the acronym has been used in the document. The `glossaries` package

also provides a means to do this on either a local or a global level. To reset an acronym, you will need to replace:

```
\resetacronym{\acr-name}
```

glossary

with either

```
\glsreset{\label}
```

glossaries

or

```
\glslocalreset{\label}
```

glossaries

To unset an acronym, you will need to replace:

```
\unsetacronym{\acr-name}
```

glossary

with either

```
\glsunset{\label}
```

glossaries

or

```
\glslocalunset{\label}
```

glossaries

To reset all acronyms, you will need to replace:

```
\resetallacronyms
```

glossary

with

```
\glsresetall[\acronymtype]
```

glossaries

or

```
\glslocalresetall[\acronymtype]
```

glossaries

To unset all acronyms, you will need to replace:

```
\unsetallacronyms
```

glossary

with

```
\glsunsetall[\acronymtype]
```

glossaries

or

```
\glslocalunsetall[\acronymtype]
```

glossaries

8 Displaying the glossary

The glossary package provides the command `\printglossary` (or `\print<type>` for other glossary types) which can be used to print individual glossaries. The glossaries package provides the command `\printglossaries` which will print all the glossaries which have been defined, or `\printglossary[<options>]` to print individual glossaries. So if you just have `\printglossary`, then you can leave it as it is, but if you have, say:

```
\printglossary  
\printglossary[acronym]
```

or

```
\printglossary  
\printacronym
```

then you will need to replace this with either

```
\printglossaries
```

or

```
\printglossary  
\printglossary[type=\acronymtype]
```

The glossary package allows you to specify a short title (for the table of contents and page header) by defining a command of the form `\short<glossary-type>name`. The

glossaries package doesn't do this, but instead provides the `toctitle` key which can be used in the optional argument to `\printglossary`. For example, if you have created a new glossary type called `notation`, and you had defined

```
\newcommand{\shortnotationname}{Notation}
```

then you would need to use the `toctitle` key:

```
\printglossary[type=notation,toctitle=Notation]
```

The `glossaries` package will ignore `\shortnotationname`, so unless you have used it elsewhere in the document, you may as well remove the definition.

9 Processing Your Document

If you convert your document from using the `glossary` package to the `glossaries` package, you will need to delete any of the additional files, such as the `.glo` file, that were created by the `glossary` package, as the `glossaries` package uses a different format. Remember also, that if you used the `makeglos` Perl script, you will need to use the `makeglossaries` Perl script instead. As from v1.17, the `glossaries` package can be used with either `makeindex` or `xindy`. Since `xindy` was designed to be multilingual, the new `glossaries` package is a much better option for non-English documents.

For further information on using `makeglossaries`, `makeindex` or `xindy` to create your glossaries, see Section 1.4 of the `glossaries` documentation.

10 Troubleshooting

Please check the FAQ⁶ for the `glossaries` package if you have any problems.

Index

F	makeglossaries	12
file types	makeindex	1, 2, 5, 7, 12
.glo	12	
G	\newglossaryentry options	
\gls options	description	8
counter	6	
number	6	
\glsadd options	name	8
counter	6	
M	package options:	
makeglos	description	8
	\printglossary options	
	style	4

⁶<http://www.dickimaw-books.com/faqs/glossariesfaq.html>

toctitle	4, 12		
			U	
	S		\useglosentry options	
\storeglosentry options			format 6
format	5	number 6
number	5	xindy 1, 7, 12
			X	